


OUTLINE

USED ON:

MATERIAL:	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	<u>P/N SUFFIX DEFINITION</u> -1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK	THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR		
	TOLERANCES AS FOLLOWS DEC. .XXX ± .005 DEC. .XX ± .010 FRACT. ± 1/64 ANGLES ± 30' CONCENTRICITY .003 TIR BREAK ALL SHARP EDGES .005 MIN. .010 MAX. MAX. SURF. ROUGHNESS: 32√	SCALE: 2:1			
FINISH:	DR: B.ERTEL		SIZE	NMV-EXT	REV
CHAMFER ALL THREADS 30° TO ROOT DIAMETER	CH: PB		A		SHEET 1 OF 1
	APP: PB	DO NOT SCALE DRAWING			
	DATE DR: 5/5/2003				