



WEIGHT = 3.25 LBM

OUTLINE

USED ON:		P/N SUFFIX DEFINITION		<div>ROCHESTER, NEW YORK</div>			
MATERIAL:		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES				THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR	
FINISH:	TOLERANCES AS FOLLOWS		SCALE: 1:1		SST300 SCREENSTAR 3X CONVERSION LENS		
	DEC. .XXX ± .005		DR: R. PODLENA				
	DEC. .XX ± .010		CH:				
	FRACT. ± 1/64		APP:				
	ANGLES ± 30'		<div><div>0.0inch1.0</div><div>0.0mm25.0</div></div> <div></div>		SIZE B		
	CONCENTRICITY .003 TIR						
	BREAK ALL SHARP EDGES .005 MIN. .010 MAX.						
	DATE DR: 2/28/2005						
CHAMFER ALL THREADS 30° TO ROOT DIAMETER		MAX. SURF. ROUGHNESS: 32		DO NOT SCALE DRAWING		REV A	
						SHEET 1 OF 1	