



OUTLINE

USED ON:								
MATERIAL:	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		P/N SUFFIX DEFINITION		<div>NAVITAR</div> <div>ROCHESTER, NEW YORK</div>			
			-1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK					
FINISH:	TOLERANCES AS FOLLOWS		SCALE: 1:1	<div><div>0.0 inch 1.0</div><div><div></div><div></div><div></div><div></div><div></div></div><div><div>0.0 mm 25.0</div><div><div></div><div></div><div></div><div></div><div></div></div></div></div>		V-GROOVE COUPLER 6X LED		
	DEC. .XXX ± .005	DR: DJM						
	DEC. .XX ± .010	CH: PB						
	FRACT. ± 1/64	APP: PB						
	ANGLES ± 30°	DATE DR: 11/15/2002						
	CONCENTRICITY .003 TIR							
	BREAK ALL SHARP EDGES							
	.005 MIN. .010 MAX.							
	MAX. SURF. ROUGHNESS: 32							
CHAMFER ALL THREADS 30° TO ROOT DIAMETER			DO NOT SCALE DRAWING	<div></div>		SIZE A	<div>3-62355_OL</div> <div>SHEET 1 OF 1</div>	REV A