

WEIGHT - 5.819 LBMASS

# OUTLINE

USED ON:

MATERIAL:

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

P/N SUFFIX DEFINITION

- 1 CONVERSION COATING
- 2 PAINTING
- 3 MARKING
- R REWORK

THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR



FINISH:

TOLERANCES AS FOLLOWS

- DEC. .XXX ± .005
- DEC. .XX ± .010
- FRACT. ± 1/64
- ANGLES ± 30'
- CONCENTRICITY .003 TIR

SCALE: 1:2


DR: DJM

CH: PB

APP: PB

DATE DR: 3/30/2004

DO NOT SCALE DRAWING



SCREENSTAR 0.65X WIDE ANGLE ADAPTER

CHAMFER ALL THREADS 30° TO ROOT DIAMETER

BREAK ALL SHARP EDGES .005 MIN. .010 MAX.

MAX. SURF. ROUGHNESS: 32



SIZE

B

1-16423

SHEET 2 OF 2

REV

C