



OUTLINE

USED ON:				 ROCHESTER, NEW YORK		
MATERIAL:	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	<u>P/N SUFFIX DEFINITION</u> -1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK	THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR			
	TOLERANCES AS FOLLOWS	SCALE: 1:1		OBJECTIVE COUPLER-MITUTOYO		
FINISH:	DEC. .XXX ± .005 DEC. .XX ± .010 FRACT. ± 1/64 ANGLES ± 30' CONCENTRICITY .003 TIR BREAK ALL SHARP EDGES .005 MIN. .010 MAX. MAX. SURF. ROUGHNESS: 32	DR: PODLENA	0.0 inch 1.0 			
		CH:		SIZE A		
		APP:				
		DATE DR: 4/4/2002		2-50025_OL SHEET 1 OF 1		
CHAMFER ALL THREADS 30° TO ROOT DIAMETER		DO NOT SCALE DRAWING	