



OUTLINE

USED ON:				
MATERIAL:	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	P/N SUFFIX DEFINITION -1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK	THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR	
	TOLERANCES AS FOLLOWS	SCALE: 1:1		
	DEC. .XXX ± .005	DR: PODLENA	0.0 inch 1.0	
	DEC. .XX ± .010	CH:	0.0 mm 25.0	
	FRACT. ± 1/64	APP:		
	ANGLES ± 30'	DATE DR: 6/11/2002		
	CONCENTRICITY .003 TIR	DO NOT SCALE DRAWING		
	BREAK ALL SHARP EDGES .005 MIN. .010 MAX.			
	MAX. SURF. ROUGHNESS: 32			



STANDARD OBJECTIVE COUPLER ASSEMBLY

SIZE	2-50026_OL	REV
A	SHEET 1 OF 1	A