




WIRE ASSIGNMENTS	
PIN	FUNCTION
1	MAX. CONTROL CURRENT +
2	MAX. CONTROL CURRENT -
3	GND
4	POWER
5	I ² C SCL
6	I ² C SDA






MALE
OPTOTUNE SIDE



FEMALE
LENS DRIVER SIDE

OUTLINE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NAVITAR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NAVITAR IS PROHIBITED.		 NAVITAR ROCHESTER, NEW YORK	
SCALE:	1:1			HIROSE CABLE, 6 PIN, M/F, 1M	
WEIGHT:	0.00 lbmass				
DR BY:	JD				
CH BY:	DEROSA	DO NOT SCALE DRAWING		SIZE	PART NUMBER
PROJECT #:	E3640			A	1-40370
DATE DR:	8/6/2019			REV	A